



The DPP is a wireless PIR (Passive Infra-Red) motion detector, designed to detect movements within an assigned area and transmit an event to the control panel. The detector is immune to animals weighing up to 25Kg.

The DPP alerts on low battery condition and has a tamper switch that activates when its enclosure is opened or removed from the mounting surface.

The DPP transmits supervision events, and has a LED that indicates on alarm event, tamper event, and low battery.

PIMA Electronic Systems' portfolio includes a wide selection of hardwired and wireless detectors, sensors and sirens for both security and safety purposes. Our products are developed with uncompromising quality, ease of installation, and operation experience.

PIMA's wireless detectors integrate the FastLink technology, an advanced wireless detection technology using true, 128-bit AES encryption that ensures maximum wireless security.

PIMA's detectors are a perfect solution for the business as well as for the home markets.

The **FORCE** and **FORCE** Lite alarm systems interface with a wide selection of expanders and peripherals, enabling the customer to expand the system as needed.

Features

- Pet immunity signal processing prevents false alarms with pets weighing up to 25kg
- Sends supervision signal every 15 minutes to the control panel
- Battery powered with low battery reporting
- Wall and cover tamper switch
- Adjustable pulse count
- Compact design for residential and commercial installations

Technical specifications

- Transmission:
 - Frequency (MHz):

DPP143: 433.92DPP187: 868.95

Output: 10mWBandwidth: 100KHzModulation: FM

One-way

Detection range: 12m/90°Pet immunity: up to 25Kg

Transmission range: 500m in open space¹
Supervision: reporting at 15-minute intervals

¹ Walls or metal may reduce actual operating range



• Tamper Event: the tamper switch's status is reported as part of every supervision report.

• Sensitivity level and LED setting (using jumpers)

Battery: 1X 3V, CR123A, Lithium

• Battery Life Cycle: up to 5 years (typical usage)

• Battery Supervision: battery status is reported as part of every supervision report

Dimensions: 11 X 5.5 X 5.5 cmWeight (excluding battery): 110gr

CE Compliance

• Operating Temperature: -10 to +50 °C

• Humidity (Max.): 93% R.H., Non-condensing

Ordering Information

• DPP143: 8831012 • DPP187: 8831025









For product information www.pima-alarms.com

All rights reserved © 2019 Pima Electronic Systems Ltd.

Manufactured by:

PIMA Electronic Systems Ltd.

5 Hatzoref Street, Holon 5885633, ISRAEL Tel: +972.3.6506414 Fax: +972.3.5500442

Email: support@pima-alarms.com

Doc no. SPC-8831012, Revision: 10-2019