



The SRO is a battery powered wireless siren for indoor and outdoor installations, designed for the **FORCE** and **FORCE Lite** intruder alarm systems. Its enclosure is made of qualified ABS material.

The SRO alerts on low battery state, and has an enclosure tamper switch. The siren transmits a test event every 15 min.

PIMA Electronic Systems' portfolio includes a wide selection of hardwired and wireless detectors, sensors and sirens for both security and safety purposes. Our products are developed with uncompromising quality, ease of installation, and operation experience.

PIMA's wireless detectors integrate the FastLink technology, an advanced wireless detection technology using true, 128-bit AES encryption that ensures maximum wireless security.

PIMA's detectors are a perfect solution for the business as well as for the home markets.

The **FORCE** and **FORCE Lite** alarm systems interface with a wide selection of expanders and peripherals, enabling the customer to expand the system as needed.

Main Features

- Qualified ABS material
- Unique mechanical design
- IP34 rating
- Battery operated
- 6 LED indicators, 4 alarm sounds with 2 different volumes.

Technical Specifications

- Transmission:
 - Frequency (MHz):
 - SRO143: 433.92
 - SRO187: 868.95
 - Output: 10mW
 - Bandwidth: 100KHz
 - Modulation: FM
- One-way
- Battery: 3X 1.5V, C size, Alkaline.
- Battery Life Expectancy: Up to 3 Years (Normal Usage)
- Alarm Sounder: 105dB at 1m
- IP Rating: 34
- Sizes: 28.5(H) X 10.5(W) X 7.5(D) cm
- CE compliance
- Weight: 1.23kg

- Operating temperature: -10 to +50 °C
- Humidity (Max.): 93% R.H., Non-condensing.

Ordering Information

- SRO143: P/N 8831016
- SRO187: P/N 8831023



For product information
www.pima-alarms.com

All rights reserved © 2019 Pima Electronic Systems Ltd.

Manufactured by:

PIMA Electronic Systems Ltd.

5 Hatzoref Street, Holon 5885633, Israel

Tel: +972.3.6506414 Fax: +972.3.5500442

Email: support@pima-alarms.com

Doc no. SPC-8831016, Revision: 10-2019